

## Specification Sheet

Part Number: 156-01714



LOC Locking Clamp, 20–25 mm, with T50SMVC Swivel Tie, PA66HIRHSUV, Black, 1000/ctn

<b>Article Number</b>	156-01714
<b>Type</b>	T50SMVCLOC20-25
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•Bundle can rotate to any orientation, allowing routing in any direction regardless of mounting point.</li><li>•Clip is reusable, making relocation or adjustments simple.</li><li>•All-in-one bundling and mounting solution reduces costs.</li></ul>
<b>Quantity Per</b>	carton
<b>Product Description</b>	HellermannTyton's 1-Piece Cable Tie with Pipe Clip secures cables to tubular frame rails. The cable tie bundles wires, cables or tubes, and the C-clip snaps onto the tubular frame rail. The clip can be removed from the mounting surface and reinstalled without additional fasteners.
<b>Short Description</b>	LOC Locking Clamp, 20–25 mm, with T50SMVC Swivel Tie, PA66HIRHSUV, Black, 1000/ctn

Global Part Name

T50SMVCLOC20-25-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

50

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

8.3

Length L (Metric)

210.0

Fixation Method

Omega Clips

Identification Plate Position

none

Width W (Metric)

12.0

Bundle Diameter Min (Imperial)

0.79

Bundle Diameter Min (Metric)

50.0

Bundle Diameter Max (Imperial)

2.0

Bundle Diameter Max (Metric)

50.0

Height H (Imperial)

1.53

Height H (Metric)

38.9

Depth D (imperial)

0.47

Depth D (metric)

12.0

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Material Cable Tie</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Flammability</b>	UL 94 HB
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Weight (Metric)</b>	3.84
<b>Weight (Imperial)</b>	0.14