

Specification Sheet

Part Number: 156-01795

Bundle can rotate to any orientation, allowing routing in any direction regardless of mounting point. 2-piece design allows installer to slide clip around cable tie to obtain optimum orientation. Clip is reusable, making relocation or adjustments simple.



2-Piece Cable Tie with Pipe Clip, .16"-.39" Attaches to Diameter, PA66HS/PA66HIRHS, Black, 500/Pkg

Article Number 156-01795

Type T50IOC1B

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's 2-Piece Cable Tie with Pipe Clip secures cables to tubular frame rails. The cable tie bundles wires, cables or tubes, and the C-clip snaps onto the tubular frame rail. The clip can be removed from the mounting surface and reinstalled without additional fasteners.

Short Description 2-Piece Cable Tie with Pipe Clip, .16"-.39" Attaches to Diameter, PA66HS/PA66HIRHS, Black, 500/Pkg

Global Part Name	T50IOC1B-PA66HS/PA66HIRHS-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	12.0
Length L (Metric)	305.0
Fixation Method	Omega Clips
Identification Plate Position	none
Bundle Diameter Min (Imperial)	0.16
Bundle Diameter Min (Metric)	4.0
Bundle Diameter Max (Imperial)	1.8
Bundle Diameter Max (Metric)	45.0
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS PA66HIRHS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)

Flammability	UL 94 HB
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)