

## Specification Sheet

Part Number: 156-01831



LOC Locking Clamp, 5-9 mm, to MOC Clip, 7 mm, PA66HIRHSUV, Black, 1000/ctn

Article Number	156-01831
Type	MOC7LOC5-9
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Patented retention design of clip features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.</li><li>• Clip and clamp both offer easy bundle installation.</li><li>• Independent rotation allows for adjustable routing orientation.</li><li>• Locking clamp dynamically fits a range of bundle sizes.</li></ul>
Quantity Per	carton

### Product Description

The MOC to LOC is a rotatable dual routing clip and clamp combination that keeps two routings secured and separated. A swivel coupler allows them to rotate independently of each other.

<b>Short Description</b>	LOC Locking Clamp, 5-9 mm, to MOC Clip, 7 mm, PA66HIRHSUV, Black, 1000/ctn
<b>Global Part Name</b>	MOC7LOC5-9-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	1.46
<b>Length L (Metric)</b>	37.20
<b>Variant</b>	Clip to Clamp
<b>Bundle Diameter Min (Imperial)</b>	0.24
<b>Bundle Diameter Min (Metric)</b>	6.0
<b>Bundle Diameter Max (Imperial)</b>	0.31
<b>Bundle Diameter Max (Metric)</b>	8.0
<b>Height H (Imperial)</b>	0.93
<b>Height H (Metric)</b>	23.6
<b>Depth D (imperial)</b>	0.47
<b>Depth D (metric)</b>	12.0
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV

<b>Flammability</b>	UL 94 HB
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Weight (Metric)</b>	2.84
<b>Weight (Imperial)</b>	0.1