

## Specification Sheet

Part Number: 156-01843



LOC Locking Clamp, 5-9 mm, to MOC Clip, 16 mm, PA66HIRHSUV, Black, 1000/ctn

**Article Number**

156-01843

**Type**

MOC16LOC5-9

**Color**

Black (BK)

**Features & Benefits**

- Patented retention design of clip features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.
- Clip and clamp both offer easy bundle installation.
- Independent rotation allows for adjustable routing orientation.
- Locking clamp dynamically fits a range of bundle sizes.

**Quantity Per**

carton

**Product Description**

The MOC to LOC is a rotatable dual routing clip and clamp combination that keeps two routings secured and separated. A swivel coupler allows them to rotate independently of each other.

|                                       |   |
|---------------------------------------|---|
| <b>Short Description</b>              | LOC Locking Clamp, 5-9 mm, to MOC Clip, 16 mm, PA66HIRHSUV, Black, 1000/ctn |
| <b>Global Part Name</b>               | MOC16LOC5-9-PA66HIRHSUV-BK  |
| <b>Length L (Imperial)</b>            | 1.85  |
| <b>Length L (Metric)</b>              | 47.10   |
| <b>Variant</b>                        | Clip to Clamp   |
| <b>Bundle Diameter Min (Imperial)</b> | 0.55  |
| <b>Bundle Diameter Min (Metric)</b>   | 14.0  |
| <b>Bundle Diameter Max (Imperial)</b> | 0.72  |
| <b>Bundle Diameter Max (Metric)</b>   | 18.3  |
| <b>Height H (Imperial)</b>            | 1.01  |
| <b>Height H (Metric)</b>              | 25.7  |
| <b>Depth D (imperial)</b>             | 0.47  |
| <b>Depth D (metric)</b>               | 12.0  |
| <b>Material</b>                       | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)    |
| <b>Material Shortcut</b>              | PA66HIRHSUV   |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>Flammability</b>                   | UL 94 HB                          |
| <b>Halogen free</b>                   | Yes                               |
| <b>Operating Temperature (Metric)</b> | -40°F to +230°F (-40°C to +110°C) |
| <b>ROHS Complaint</b>                 | Yes                               |
| <b>Package Quantity(Imperial)</b>     | 1000                              |
| <b>Package Quantity (Metric)</b>      | 1000                              |
| <b>Customs Number</b>                 | 3926909988                        |
| <b>Weight (Metric)</b>                | 4.14                              |
| <b>Weight (Imperial)</b>              | 0.15                              |