

Specification Sheet

Part Number: 156-01863



LOC Locking Clamp, 10-14 mm, to MOC Clip, 12 mm, PA66HIRHSUV, Black, 1000/ctn

Article Number

156-01863

Type

MOC12LOC10-14

Color

Black (BK)

Features & Benefits

- Patented retention design of clip features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.
- Clip and clamp both offer easy bundle installation.
- Independent rotation allows for adjustable routing orientation.
- Locking clamp dynamically fits a range of bundle sizes.

Quantity Per

carton

Product Description

The MOC to LOC is a rotatable dual routing clip and clamp combination that keeps two routings secured and separated. A swivel coupler allows them to rotate independently of each other.

Short Description

LOC Locking Clamp, 10-14 mm, to MOC Clip, 12 mm, PA66HIRHSUV, Black, 1000/ctn

Global Part Name

MOC12LOC10-14-PA66HIRHSUV-BK

Length L (Imperial)

1.86

Length L (Metric)

47.30

Variant

Clip to Clamp

Bundle Diameter Min (Imperial)

0.41

Bundle Diameter Min (Metric)

10.5

Bundle Diameter Max (Imperial)

0.54

Bundle Diameter Max (Metric)

13.8

Height H (Imperial)

1.08

Height H (Metric)

27.4

Depth D (imperial)

0.47

Depth D (metric)

12.0

Material

Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut

PA66HIRHSUV

Flammability	UL 94 HB
Halogen free	Yes
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Weight (Metric)	4.3
Weight (Imperial)	0.15