

Specification Sheet

Part Number: 156-01871



LOC Locking Clamp, 10-14 mm, to MOC Clip, 22 mm, PA66HIRHSUV, Black, 1000/ctn

Article Number

156-01871

Type

MOC22LOC10-14

Color

Black (BK)

Features & Benefits

- Patented retention design of clip features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.
- Clip and clamp both offer easy bundle installation.
- Independent rotation allows for adjustable routing orientation.
- Locking clamp dynamically fits a range of bundle sizes.

Quantity Per

carton

Product Description

The MOC to LOC is a rotatable dual routing clip and clamp combination that keeps two routings secured and separated. A swivel coupler allows them to rotate independently of each other.

Short Description

LOC Locking Clamp, 10-14 mm, to MOC Clip, 22 mm, PA66HIRHSUV, Black, 1000/ctn

Global Part Name

MOC22LOC10-14-PA66HIRHSUV-BK

Length L (Imperial)

2.21

Length L (Metric)

56.20

Variant

Clip to Clamp

Bundle Diameter Min (Imperial)

0.79

Bundle Diameter Min (Metric)

20.0

Bundle Diameter Max (Imperial)

0.98

Bundle Diameter Max (Metric)

25.0

Height H (Imperial)

1.44

Height H (Metric)

36.5

Depth D (imperial)

0.47

Depth D (metric)

12.0

Material

Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut

PA66HIRHSUV

Flammability	UL 94 HB
Halogen free	Yes
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Weight (Metric)	6.34
Weight (Imperial)	0.22