

Specification Sheet

Part Number: 156-01873



LOC Locking Clamp, 10-14 mm, to MOC Clip, 26 mm, PA66HIRHSUV, Black, 1000/ctn

Article Number

156-01873

Type

MOC26LOC10-14

Color

Black (BK)

Features & Benefits

- Patented retention design of clip features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.
- Clip and clamp both offer easy bundle installation.
- Independent rotation allows for adjustable routing orientation.
- Locking clamp dynamically fits a range of bundle sizes.

Quantity Per

carton

Product Description

The MOC to LOC is a rotatable dual routing clip and clamp combination that keeps two routings secured and separated. A swivel coupler allows them to rotate independently of each other.

| | |
|---------------------------------------|---|
| Short Description | LOC Locking Clamp, 10-14 mm, to MOC Clip, 26 mm, PA66HIRHSUV, Black, 1000/ctn |
| Global Part Name | MOC26LOC10-14-PA66HIRHSUV-BK |
| Length L (Imperial) | 2.49 |
| Length L (Metric) | 63.20 |
| Variant | Clip to Clamp |
| Bundle Diameter Min (Imperial) | 0.91 |
| Bundle Diameter Min (Metric) | 23.0 |
| Bundle Diameter Max (Imperial) | 1.14 |
| Bundle Diameter Max (Metric) | 29.0 |
| Height H (Imperial) | 1.61 |
| Height H (Metric) | 41.0 |
| Depth D (imperial) | 0.47 |
| Depth D (metric) | 12.0 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |

| | |
|---------------------------------------|-----------------------------------|
| Flammability | UL 94 HB |
| Halogen free | Yes |
| Operating Temperature (Metric) | -40°F to +230°F (-40°C to +110°C) |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Weight (Metric) | 7.04 |
| Weight (Imperial) | 0.25 |