

Specification Sheet

Part Number: 156-01928



MOC Clip to MOC Clip Perpendicular, 5 mm, 9 mm Perpendicular, PA66HIRHSUV, Black, 2000/ctn

Article Number 156-01928

Type MOC5FMOC9M180

Color Black (BK)

Features & Benefits

- Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.
- Controlled flex and angled entry promote easy installation.
- Independent rotation allows for adjustable routing orientation.

Quantity Per carton

Product Description

The MOC to MOC 180 is a rotatable dual routing clip that keeps two routings secured and separated. One clip is orientated 90 degrees from the other to provide alternative access for bundle attachment. A swivel coupler allows them to rotate independently of each other.

| | |
|---------------------------------------|--|
| Short Description | MOC Clip to MOC Clip Perpendicular, 5 mm, 9 mm Perpendicular, PA66HIRHSUV, Black, 2000/ctn |
| Global Part Name | MOC5FMOC9M180-PA66HIRHSUV-BK |
| Length L (Imperial) | 1.26 |
| Length L (Metric) | 31.97 |
| Variant | Clip to Clip Transverse |
| Bundle Diameter Min (Imperial) | 0.16 |
| Bundle Diameter Min (Metric) | 4.0 |
| Bundle Diameter Max (Imperial) | 0.22 |
| Bundle Diameter Max (Metric) | 5.5 |
| Height H (Imperial) | 0.59 |
| Height H (Metric) | 15.0 |
| Depth D (Imperial) | 0.39 |
| Depth D (Metric) | 10.0 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |

| | |
|------------------------------------|-----------------------------------|
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| Halogen Free | Yes |
| Operating Temperature | -40°F to +230°F (-40°C to +110°C) |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 2000 |
| Package Quantity (Metric) | 2000 |
| Customs Number | 3926909988 |
| Weight (Metric) | 1.44 |
| Weight (Imperial) | 0.05 |