

Specification Sheet

Part Number: 156-02265



2-Piece Cable Tie/Fir Tree Mount, Unassembled Set, 80mm Max Bundle, PA66HIRHSUV, Black, 3000/ctn

Article Number	156-02265
Type	T50ISADFTOVAL-SET
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Bi-directional saddle allows for the securing of bundles perpendicular or parallel to mounting hole.• HellermannTyton's 4x oval prevents bundle rotation while providing best-in-class installation and extraction resistance for four common oval sizes.
Quantity Per	carton

Product Description

These two-piece fasteners offer a simple and versatile method of bundling and mounting cables up to 4.3" (110 mm) to a panel up to 6.0 mm thick using an oval hole. The fir tree will easily push into pre-punched holes in panels or threaded blind holes and offers a secure fit. The two-piece design enables the head of the tie to be oriented in the required position to ease assembly, while the disc on top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Short Description

2-Piece Cable Tie/Fir Tree Mount, Unassembled Set, 80mm Max Bundle, PA66HIRHSUV, Black, 3000/ctn

Global Part Name

T50ISADFTOVAL-SET-PA66HS/PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225.0

Length L (Imperial)

7.95

Length L (Metric)

202.0

Fixation Method

Fir Tree for oval holes

Identification Plate Position

none

Tie Closure

plastic pawl

Width W (Imperial)

0.694

Width W (Metric)

17.63

Bundle Diameter Min (Imperial)

0.197

Bundle Diameter Min (Metric)

5.0

Bundle Diameter Max (Imperial)

3.15

Bundle Diameter Max (Metric)

80.0

Height H (Imperial)

0.787

Height H (Metric)	20.0
Mounting Hole Diameter D (Imperial)	0.24 " X 0.48 " 0.26 " X 0.49 " 0.26 " X 0.51 " 0.28 " X 0.47
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm 6.5 x 12.5 mm 7.0 x 12.0 mm 6.2 x 12.2 mm
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HIRHS PA66HS
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988