

Specification Sheet

Part Number: 156-02380

Once installed, perpendicular arrowhead arms reduce movement and will not collapse when exposed to water or load

Integrated dual seal meets IP65 for protection against water, dust, chemicals, air and sound

15 mm and 25 mm offset designs fasten bundles away from obstructions, heat or sources of abrasion

Superior design and high-spec materials maintain routing position to deliver consistent performance in the most rugged applications

Low-profile design saves 5 mm of height when installed

All ties rated to 222 N (50 lb) tensile strength to ensure long-term bundling reliability

Sealed arrowhead meets USCAR44 push in, pull off and sealing standards



2-Pc Tie/Arrowhead Mnt w/Seal, 1.2 - 1.8mm panel, 6.5mm/6.35mm HEX, PA66HS/TPE, Black/Gray, 2000/ctn

Article Number	156-02380
Type	T50RSRAH6.5D1.4TSD
Color	Black (BK) Gray (GY)
Quantity Per	bag

Product Description	HellermannTyton sealed clips and ties are constructed of engineered nylon with a dual TPE (thermo plastic elastomer) seal. The combination of dual seal and engineered arrowhead provide superior sealing performance for applications where protection from moisture and debris is essential.
Short Description	2-Pc Tie/Arrowhead Mnt w/Seal, 1.2 - 1.8mm panel, 6.5mm/6.35mm HEX, PA66HS/TPE, Black/Gray, 2000/ctn
Global Part Name	T50RSRAH6.5D1.4TSD-PA66HS/TPE-BK/GY
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	8.0
Length L (Metric)	202.0
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.87
Width W (Metric)	22.3

Bundle Diameter Min (Imperial)	0.12
Bundle Diameter Min (Metric)	3.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	.59
Height H (Metric)	15.08
Panel Thickness Min (Imperial)	0.04
Panel Thickness Max (Imperial)	0.07
Panel Thickness Min (Metric)	1.2
Panel Thickness Max (Metric)	1.8
Mounting Hole Diameter D (Imperial)	0.25 " (hexagonal) 0.25
Mounting Hole Diameter D (Metric)	6.5 mm 6.35 mm (hexagonal)
Disc Diameter (Metric)	22,3
Material	Thermoplastic Elastomer (TPE) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	TPE PA66HS

Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +257°F (-40°C to +125°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	2000
Package Quantity (Metric)	2000
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)