

## Specification Sheet

Part Number: 156-02384



LOC Locking Clamp, 5–9 mm, with T50SMVC Swivel Tie, PA66HIRHSUV, Black, 1000/ctn

<b>Article Number</b>	156-02384
<b>Type</b>	T50SMVCLOC5-9
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•Bundle can rotate to any orientation, allowing routing in any direction regardless of mounting point.</li><li>•Clip is reusable, making relocation or adjustments simple.</li><li>•All-in-one bundling and mounting solution reduces costs.</li></ul>
<b>Quantity Per</b>	carton
<b>Product Description</b>	HellermannTyton's 1-Piece Cable Tie with Pipe Clip secures cables to tubular frame rails. The cable tie bundles wires, cables or tubes, and the C-clip snaps onto the tubular frame rail. The clip can be removed from the mounting surface and reinstalled without additional fasteners.
<b>Short Description</b>	LOC Locking Clamp, 5–9 mm, with T50SMVC Swivel Tie, PA66HIRHSUV, Black, 1000/ctn

Global Part Name

T50SMVCLOC5-9-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

50

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

8.3

Length L (Metric)

210.0

Fixation Method

Omega Clips

Identification Plate Position

none

Width W (Imperial)

0.47

Width W (Metric)

12.00

Bundle Diameter Min (Imperial)

0.20

Bundle Diameter Min (Metric)

50.0

Bundle Diameter Max (Imperial)

2.0

Bundle Diameter Max (Metric)

50.0

Height H (Imperial)

1.08

Height H (Metric)

23.6

Depth D (imperial)

0.47

Depth D (metric)

12.0

**Mounting Hole Diameter D (Imperial)**

0.2 " - 0.35

**Mounting Hole Diameter D (Metric)**

5.0-9.0 mm

**Material**

Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut**

PA66HIRHSUV

**Material Cable Tie**

Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

**Flammability**

UL 94 HB

**Halogen free**

Yes

**Operating Temperature (Metric)**

-40°F to +230°F (-40°C to +110°C)

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

1000

**Package Quantity (Metric)**

1000

**Weight (Metric)**

2.21

**Weight (Imperial)**

0.08

