


## Specification Sheet

Part Number: 156-02434

Versatile and robust fir tree design provides low insertion effort yet delivers exceptional retention strength in an 6.5 mm hole and M8 threaded hole.

Wider and thinner strap design increases flexibility and minimizes pinching of bundles, hoses and tubing.

PA46 nylon material provides great performance at up to 135°F continuous operating temperature.



2-Piece Cable Tie/Fir Tree Mount, 6.5mm Hole and M8 Threaded Hole, PA46, Brown, 1200/ctn

<b>Article Number</b>	156-02434
<b>Type</b>	WSSDFTM8WSSDSET
<b>Color</b>	Brown (BN)
<b>Quantity Per</b>	carton
<b>Product Description</b>	These two-piece fasteners are pre-assembled and offer a simple and versatile method of bundling and mounting cables. Sold as an unassembled set, this oval fir tree and tie combination allows the user to install the tie in two different directions, securing the bundle perpendicular or inline to the oval mounting hole.
<b>Short Description</b>	2-Piece Cable Tie/Fir Tree Mount, 6.5mm Hole and M8 Threaded Hole, PA46, Brown, 1200/ctn

**Global Part Name**

WSSDFTM8WSSDSET-PA46-BN

**Minimum Tensile Strength (Imperial)**

120.0

**Minimum Tensile Strength (Metric)**

533.0

**Length L (Imperial)**

9.1

**Length L (Metric)**

231.14

**Fixation Method**

Fir Tree

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.88

**Width W (Metric)**

22.6

**Bundle Diameter Min (Imperial)**

0.37

**Bundle Diameter Min (Metric)**

9.4

**Bundle Diameter Max (Imperial)**

2.25

**Bundle Diameter Max (Metric)**

57.15

<b>Height H (Imperial)</b>	0.89
<b>Height H (Metric)</b>	22.77
<b>Panel Thickness Min (Imperial)</b>	0.02
<b>Panel Thickness Max (Imperial)</b>	0.23
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	6.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.25
<b>Mounting Hole Diameter D (Metric)</b>	M8 6.5 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.27
<b>Material</b>	Polyamide 4.6 (PA46)
<b>Material Shortcut</b>	PA46
<b>Flammability</b>	UL 94 V-2
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-40°F to +266°F (-40°C to +130°C)

<b>Reach Compliant (Article 33)</b>	No
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	1200
<b>Package Quantity (Metric)</b>	1200
<b>Customs Number</b>	3926909988