

Specification Sheet

Part Number: 156-02451



Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.

Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

Two-piece assembly allows the mount to slide along the strap ensuring proper orientation.

2-Piece Cable Tie & Edge Clip, 8.0" Long, EC5B, 1–3 mm Panel, 45lb, PA12/PA66HIRHSUVR5, Black, 500/pkg

Article Number 156-02451

Type T50REC5B

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's Two-Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place. NOTE: UL Listing applies to 1-2mm panel thicknesses only.

Short Description 2-Piece Cable Tie & Edge Clip, 8.0" Long, EC5B, 1–3 mm Panel, 45lb, PA12/PA66HIRHSUVR5, Black, 500/pkg

Global Part Name	T50REC5B-PA12/PA66HIRHSUVR5-BK
Minimum Tensile Strength (Imperial)	45.0
Minimum Tensile Strength (Metric)	200
Length L (Imperial)	8.0
Length L (Metric)	203.2
Fixation Method	EdgeClip, sideways, assembled, 2 piece
Identification Plate Position	none
Releasable Closure	No
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.20
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	2.0
Bundle Diameter Max (Metric)	50.0
Thickness T (Imperial)	0.05

Thickness T (Metric)	1.2
Height H (Imperial)	0.61
Height H (Metric)	15.5
Panel Thickness Min (Imperial)	0.04
Panel Thickness Max (Imperial)	0.12
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	3.0
Material	Polyamide 6.6, high impact modified, heat and UV-stabilized, proprietary blend (PA66HIRHSUVR5) Polyamide 12 (PA12)
Material Shortcut	PA66HIRHSUVR5 PA12
Material Cable Tie	Polyamide 12 (PA12)
Flammability	UL 94 HB
Halogen Free	No
Operating Temperature	-40°F to +239°F (-40°C to +115°C) -40°F to +248°F (-40°C to +120°C)
ROHS Compliant	Yes

UL Listed (US and Canada) Yes

UL Listed (US) Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988