

## Specification Sheet

Part Number: 156-02490



MOC Clip to MOC Clip, 22 mm, 22 mm, PA66HIRHSUV, Black, 1500/ctn

**Article Number** 156-02490

**Type** MOC22FMOC22M

**Color** Black (BK)

**Features & Benefits**

- Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.
- Controlled flex and angled entry promote easy installation.
- Independent rotation allows for adjustable routing orientation.

**Quantity Per** carton

**Product Description**

The MOC to MOC is a rotatable dual routing clip that keeps two routings secured and separated. A swivel coupler allows them to rotate independently of each other.

<b>Short Description</b>	MOC Clip to MOC Clip, 22 mm, 22 mm, PA66HIRHSUV, Black, 1500/ctn
<b>Global Part Name</b>	MOC22FMOC22M-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	2.57
<b>Length L (Metric)</b>	65.4
<b>Variant</b>	Clip to Clip
<b>Width W (Metric)</b>	12.0
<b>Bundle Diameter Min (Imperial)</b>	0.79
<b>Bundle Diameter Min (Metric)</b>	20.0
<b>Bundle Diameter Max (Imperial)</b>	0.98
<b>Bundle Diameter Max (Metric)</b>	25.0
<b>Height H (Imperial)</b>	1.44
<b>Height H (Metric)</b>	36.5
<b>Depth D (Imperial)</b>	0.47
<b>Depth D (Metric)</b>	12.0
<b>Diameter D (Metric)</b>	22.1

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	1500
<b>Package Quantity (Metric)</b>	1500
<b>Customs Number</b>	3926909988
<b>Weight (Metric)</b>	7.34
<b>Weight (Imperial)</b>	0.26