

## Specification Sheet

Part Number: 156-02513



Cable Tie with Button Mount, 0.35" Hole Dia, 0.12" Max Panel, 0.07" Max Tie Width, PA66HIRHSUV, Blk, 1000/pkg

**Article Number**

156-02513

**Type**

T50RPBM9SET

**Color**

Black (BK)

**Features & Benefits**

- Capable of holding several cables, depending on cable tie size, for ultimate flexibility.
- Zero-insertion-force design requires no tools for quick and easy mounting.
- High impact modified, heat-resistant, UV stabilized material is ideal for long-term performance, even in extreme weather.

**Quantity Per**

bag

**Product Description**

This button head mount includes a cable tie to secure cables and wire bundles to panels. Once placed through the panel hole, installers can insert the cable tie through the mount on the panel's opposite surface. The button head mount is designed to fit pre-stamped oval hole sizes from 9x12 mm to 9x14 mm with zero insertion force. Made from impact-modified, heat-resistant, UV stabilized Polyamide 6.6 material, it will withstand extreme environments.

**Short Description**

Cable Tie with Button Mount, 0.35" Hole Dia, 0.12" Max Panel, 0.07" Max Tie Width, PA66HIRHSUV, Blk, 1000/pkg

**Global Part Name**

T50RPBM9SET-PA66HIRHSUV-BK

**Minimum Tensile Strength (Imperial)**

50.0

**Minimum Tensile Strength (Metric)**

225.0

**Length L (Imperial)**

8.0

**Length L (Metric)**

203.2

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Width W (Imperial)**

0.67

**Width W (Metric)**

17.0

**Bundle Diameter Max (Imperial)**

1.97

**Bundle Diameter Max (Metric)**

50.0

**Cable Ties**

T50R

**Height H (Imperial)**

0.53

**Height H (Metric)**

13.40

<b>Panel Thickness Max(Imperial)</b>	0.12
<b>Panel Thickness Max (Metric)</b>	3.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.35 x 0.47 ", 0.35 x 0.55
<b>Mounting Hole Diameter D (Metric)</b>	9.0 x 14.0 mm 9.0 x 12.0 mm
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Complaint</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Listed (US and Canada)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>UL Listed (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000

**Customs Number**

3926909988

---

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)