

Specification Sheet

Part Number: 156-02535



Bundle can rotate to any orientation, allowing routing in any direction regardless of mounting point.

Clip is reusable, making relocation or adjustments simple.

All-in-one bundling and mounting solution reduces costs.

1-Piece Cable Tie with Pipe Clip 5mm, 6.0" Tie, 50lb Tensile Strength, PA66HIRHSUV, BK, 500/pkg

Article Number 156-02535

Type T50SVC5

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's simple to use Wire and Swivel Clip Tie allows the attaching of wires or hoses to an existing harness. Designed for 360 degree rotation and the ability to be oriented in any direction in relation to the main harness. This is ideally suited for any application in which the wire or hose can move in relation to the attachment point.

Short Description 1-Piece Cable Tie with Pipe Clip 5mm, 6.0" Tie, 50lb Tensile Strength, PA66HIRHSUV, BK, 500/pkg

Global Part Name T50SVC5-PA66HIRHSUV/PA66HS-BK

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 222.0

Length L (Imperial) 6.1

Length L (Metric) 155.0

Fixation Method Omega Clips

Identification Plate Position none

Releasable Closure No

Width W (Imperial) 0.19

Width W (Metric) 4.7

Bundle Diameter Min (Imperial) 0.04

Bundle Diameter Min (Metric) 1.0

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 35.0

Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV PA66HS
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988