

## Specification Sheet

Part Number: 156-02604



Head allows for a lateral adjustment on stud during installation.  
Quick and easy installation ideal for manufacturing environment.

2-Piece Cable Tie/Stud Mount, 8.0"L, .25" Stud Mount, PA66HIRHSUV/Celcon M90, Black, 2,000/ctn

**Article Number** 156-02604

**Type** T50ROSSBXL6USET

**Color** Black (BK)

**Quantity Per** carton

**Product Description** With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. The Stud Mount's special design allows for a lateral adjustment, to correct any misalignment of the stud or incorrect position of the tie on the cables.

**Short Description** 2-Piece Cable Tie/Stud Mount, 8.0"L, .25" Stud Mount, PA66HIRHSUV/Celcon M90, Black, 2,000/ctn

**Global Part Name** T50ROSSBXL6USET-PA66HIRHS/POM-BK

**Minimum Tensile Strength (Imperial)** 50.0

**Minimum Tensile Strength (Metric)** 222.0

**Length L (Imperial)** 8.0

**Length L (Metric)** 203.0

**Fixation Method** Weld Stud Fixing

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Bundle Diameter Min (Imperial)** 0.16

**Bundle Diameter Min (Metric)** 4.0

**Bundle Diameter Max (Imperial)** 1.77

**Bundle Diameter Max (Metric)** 45.0

**Height H (Imperial)** 1.38

**Height H (Metric)** 35.0

**Stud Diameter (Metric)** 6.0 mm

<b>Stud Diameter (Imperial)</b>	0.25
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyacetal (POM)
<b>Material Shortcut</b>	POM PA66HIRHS
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	2000
<b>Package Quantity (Metric)</b>	2000
<b>Customs Number</b>	3926909988