

## Specification Sheet

Part Number: 156-02608

Pre-assembled 2-piece fixing tie with fir tree foot part

Cable tie head can be moved after bundling

Easy to assemble without the need for a tool

Disc adjusts tie for pressure from various directions and minimises ingress of dust and dirt

Fir tree foot part can be used for a variety of panel thicknesses

Product Image

Suitable for use within threaded holes

2-Piece Cable Tie/Fir Tree Mount, 5.9"L, .18"-.20" Mounting Hole Diameter, PA66HS and PA66HIRHS, Black, 500/pkg

**Article Number**

156-02608

**Type**

T50SOSFT5SD

**Color**

Black (BK)

**Quantity Per**

carton

**Product Description**

Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.

**Short Description**

2-Piece Cable Tie/Fir Tree Mount, 5.9"L, .18"-.20" Mounting Hole Diameter, PA66HS and PA66HIRHS, Black, 500/pkg

**Global Part Name**

T50SOSFT5SD-PA66HS/PA66HIRHS-BK

<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225.0
<b>Length L (Imperial)</b>	5.9
<b>Length L (Metric)</b>	150.0
<b>Fixation Method</b>	Fir Tree
<b>Identification Plate Position</b>	none
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Outside Serrated
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.063
<b>Bundle Diameter Min (Metric)</b>	1.6
<b>Bundle Diameter Max (Imperial)</b>	1.4
<b>Bundle Diameter Max (Metric)</b>	35.0
<b>Thickness T (Imperial)</b>	0.05
<b>Thickness T (Metric)</b>	1.3

<b>Panel Thickness Min (Imperial)</b>	0.003
<b>Panel Thickness Max (Imperial)</b>	0.12
<b>Panel Thickness Min (Metric)</b>	0.70
<b>Panel Thickness Max (Metric)</b>	3.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.18 - 0.20
<b>Mounting Hole Diameter D (Metric)</b>	4.5 - 5.0 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.18
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.20
<b>Mounting Hole Diameter D Max (Metric)</b>	5.0
<b>Disc Diameter (Metric)</b>	16.0
<b>Disc Diameter (Imperial)</b>	0.63
<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HS PA66HIRHS
<b>Material Cable Tie</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Flammability</b>	UL 94 HB

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 500

**Package Quantity (Metric)** 500

**Customs Number** 3926909988