

Specification Sheet

Part Number: 156-02632



In-Line Ratchet Clamp, 0.50" - 0.77" Bundle Dia, FT9X17, PA66HIRHSUV, Black, 250/ctn

Article Number

156-02632

Type

IRCBFT9X17

Color

Black (BK)

Features & Benefits

- One-piece ratchet closure allows for easy installation during pre- or final assembly.
- Easy release feature simplifies quick adjustments and maintenance.
- Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.
- High-performing oval fir trees ensure anti-rotational routing in existing or stamped oval or rectangular holes with no additional hardware required.

Quantity Per

bag

Product Description

The In-line Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. Built-in attachments include round and oval fir trees and adhesive mounts, so no additional hardware is needed for securing to a hole or panel. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal of cables simply by using a flat-head screwdriver. In this way, the clamp can be reused or serviced without removing it from the mounting surface. The clamp is offered in four sizes to accommodate bundles from 0.25" to 2" in diameter.

Short Description

In-Line Ratchet Clamp, 0.50" - 0.77" Bundle Dia, FT9X17, PA66HIRHSUV, Black, 250/ctn

Global Part Name

IRCBFT9X17-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

100.0

Minimum Tensile Strength (Metric)

445.0

Length L (Imperial)

1.37

Length L (Metric)

34.8

Fixation Method

Fir Tree for oval holes

Width W (Imperial)

1.37

Width W (Metric)

34.9

Bundle Diameter Min (Imperial)

0.50

Bundle Diameter Min (Metric)

12.70

Bundle Diameter Max (Imperial)

0.77

Bundle Diameter Max (Metric)

19.56

Panel Thickness Min(Imperial) 0.02

Panel Thickness Max(Imperial) 0.27

Panel Thickness Min (Metric) 0.60

Panel Thickness Max (Metric) 6.75

Mounting Hole Diameter D (Imperial) 0.35 x 0.67

Mounting Hole Diameter D (Metric) 9.0 x 17.0 mm

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Operating Temperature (Metric) -40°F to +257°F (-40°C to +125°C)

ROHS Complaint Yes

Package Quantity(Imperial) 250

Package Quantity (Metric) 250

