

Specification Sheet

Part Number: 156-02703



2-Piece M12 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HIRHSUV, BK, 1000/pkg

Article Number 156-02703

Type T50R0SBS12SET

Color Black (BK)

Features & Benefits

- Versatile design allows cable routing above, perpendicular or parallel to stud.
- Can mount up to three bundles simultaneously, making efficient use of a single mounting point.
- Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.

Quantity Per carton

| | |
|--|---|
| Product Description | Unique, two-piece design allows routing to be above, parallel or perpendicular to stud. This also enables up to three separate bundles to be fastened to the same stud. PA46 material option for high-temperature applications. This two-piece fastener offers the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. |
| Short Description | 2-Piece M12 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HIRHSUV, BK, 1000/pkg |
| Global Part Name | T50R0SBS12SET-PA66HIRHSUV-BK |
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 224.0 |
| Length L (Imperial) | 8.0 |
| Length L (Metric) | 203.2 |
| Fixation Method | Stud Mount |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Width W (Imperial) | 1.25 |
| Width W (Metric) | 32.0 |
| Bundle Diameter Min (Imperial) | 0.39 |

| | |
|---------------------------------------|--|
| Bundle Diameter Min (Metric) | 10.0 |
| Bundle Diameter Max (Imperial) | 1.77 |
| Bundle Diameter Max (Metric) | 45.0 |
| Height H (Imperial) | 0.80 |
| Height H (Metric) | 20.4 |
| Stud Diameter (Metric) | 12.0 mm |
| Stud Diameter (Imperial) | 0.47 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Material Cable Tie | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Flammability | UL 94 HB |
| Operating Temperature (Metric) | -40°F to +221°F (-40°C to +105°C) |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 1000 |

| | |
|----------------------------------|------------|
| Package Quantity (Metric) | 1000 |
| Customs Number | 3926909988 |
| Weight (Metric) | 0.0045 |
| Weight (Imperial) | 0.010 |

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)