

## Specification Sheet

Part Number: 156-02722



In-Line Ratchet Clamp, 0.24" - 0.54" Bundle Dia, MB5A, PA66HIRHSUV, Black, 25/box

Article Number	156-02722
Type	IRCAMB5A
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• One-piece ratchet closure allows for easy installation during pre- or final assembly.</li><li>• Easy release feature simplifies quick adjustments and maintenance.</li><li>• Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.</li><li>• 3M™ VHB™ adhesive on base creates an incredible bond with mounting surface.</li></ul>
Quantity Per	bag

**Product Description**

The In-line Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. Built-in attachments include round and oval fir trees and adhesive mounts, so no additional hardware is needed for securing to a hole or panel. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal of cables simply by using a flat-head screwdriver. In this way, the clamp can be reused or serviced without removing it from the mounting surface. The clamp is offered in four sizes to accommodate bundles from 0.25" to 2" in diameter.

**Short Description**

In-Line Ratchet Clamp, 0.24" - 0.54" Bundle Dia, MB5A, PA66HIRHSUV, Black, 25/box

**Global Part Name**

IRCAMB5A-PA66HIRHSUV-BK

**Minimum Tensile Strength (Imperial)**

100.0

**Minimum Tensile Strength (Metric)**

445.0

**Length L (Imperial)**

1.37

**Length L (Metric)**

34.8

**Fixation Method**

Adhesive

**Width W (Imperial)**

1.37

**Width W (Metric)**

34.9

**Bundle Diameter Min (Imperial)**

0.24

**Bundle Diameter Min (Metric)**

6.10

**Bundle Diameter Max (Imperial)**

0.54

**Bundle Diameter Max (Metric)**

13.72

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Adhesive</b>	Acrylic
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +257°F (-40°C to +125°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25