

Specification Sheet

Part Number: 156-02843

Multi-option dual-clamp stud mount secures two bundles running alongside a bolt or stud.

The 360-degree locking enclosure and cable tie dynamically fit a range of bundle sizes.

Clamp can be opened for bundle maintenance.

Independent rotation allows for adjustable routing orientation.

High-performance stud mount design allows for easy installation and delivers outstanding stud retention to keep bundles secure.



Dual Clip Stud Mount to LOC Locking Clamp, 10-14mm Clamp, 5mm/6mm Std Mnt, PA66HIRHSUV, Bk, 1000/ctn

Article Number	156-02843
Type	SMF2LOC10-14X2
Color	Black (BK)
Quantity Per	bag
Product Description	The dual LOC with stud mount features two of HellermannTyton's locking option clamps with a best-in-class stud mount to secure to a 5mm or 6mm stud or bolt. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point.
Short Description	Dual Clip Stud Mount to LOC Locking Clamp, 10-14mm Clamp, 5mm/6mm Std Mnt, PA66HIRHSUV, Bk, 1000/ctn

Global Part Name SMF2LOC10-14X2-PA66HIRHSUV-BK

Length L (Imperial) 4.22

Length L (Metric) 107.3

Fixation Method Stud Mount

Releasable Closure No

Bundle Diameter Min (Imperial) 0.39

Bundle Diameter Min (Metric) 10.0

Bundle Diameter Max (Imperial) 0.59

Bundle Diameter Max (Metric) 15.0

Height H (Imperial) 1.37

Height H (Metric) 34.9

Depth D (Imperial) 0.61

Depth D (Metric) 15.5

Nominal Diameter (Imperial) 0.47

Nominal Diameter (Metric) 12.0

Mounting Hole Diameter D (Metric) 5.0 mm 6.0 mm

Stud Diameter (Metric)	5.0 mm 6.0 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar,

electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)