

## Specification Sheet

Part Number: 156-03013



Three-piece wide strap tie and coupler assembly bundles and separates two routings at any angle from parallel to 90 degrees from each other. Wide strap ties minimize pinching of soft hoses and convoluted tubing, while the coupler protects routings from friction and abrasion.

Space-saving coupler means more room for routings.

3-Pc Wide Strap Tie with Coupler, 9.1" Long, 0.37" - 2.25" Dia, 120lbs, PA46, Brown, 100/bg

Article Number	156-03013
Type	DUALWSSASSY
Color	Brown (BN)
Quantity Per	bag
Product Description	Couplers simplify connecting two cable ties for routing and separating bundles. Designed to allow up to 90 degrees of rotation, these assemblies are ideal for applications in which the bundle, pipe or hose requires slight movement in relation to the fastening point. Manufactured using PA46 high-heat material.
Short Description	3-Pc Wide Strap Tie with Coupler, 9.1" Long, 0.37" - 2.25" Dia, 120lbs, PA46, Brown, 100/bg
Global Part Name	DUALWSSASSY-PA46-BN

Minimum Tensile Strength (Imperial)	120.0
Minimum Tensile Strength (Metric)	535
Length L (Imperial)	9.1
Length L (Metric)	231.0
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.5
Width W (Metric)	12.7
Bundle Diameter Min (Imperial)	0.6
Bundle Diameter Min (Metric)	15.0
Bundle Diameter Max (Imperial)	2.0
Bundle Diameter Max (Metric)	51.0
Height H (Imperial)	0.43
Height H (Metric)	10.86
Material	Polyamide 4.6 (PA46)

Material Shortcut	PA46
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +266°F (-40°C to +130°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)