

## Specification Sheet

Part Number: 156-03014



Three-piece wide strap tie and coupler assembly bundles and separates two routings at any angle from parallel to 90 degrees from each other. Wide strap ties minimize pinching of soft hoses and convoluted tubing, while the coupler protects routings from friction and abrasion. Space-saving coupler means more room for routings.

3-Pc Wide Strap Tie with Coupler, 15.1", 0.37" - 4.12" Dia, 120lbs, PA66HIRHSUV, Black, 100/bag

<b>Article Number</b>	156-03014
<b>Type</b>	DUALWSRASSY
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	carton
<b>Product Description</b>	Couplers simplify connecting two cable ties for routing and separating bundles. Designed to allow up to 90 degrees of rotation, these assemblies are ideal for applications in which the bundle, pipe or hose requires slight movement in relation to the fastening point.
<b>Short Description</b>	3-Pc Wide Strap Tie with Coupler, 15.1", 0.37" - 4.12" Dia, 120lbs, PA66HIRHSUV, Black, 100/bag
<b>Global Part Name</b>	DUALWSRASSY-PA66HIRHSUV-BK

<b>Minimum Tensile Strength (Metric)</b>	533
<b>Length L (Imperial)</b>	15.1
<b>Length L (Metric)</b>	383
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	1.06
<b>Width W (Metric)</b>	27.0
<b>Bundle Diameter Min (Imperial)</b>	0.375
<b>Bundle Diameter Min (Metric)</b>	9.525
<b>Bundle Diameter Max (Imperial)</b>	4.125
<b>Bundle Diameter Max (Metric)</b>	104.1
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 100

**Package Quantity (Metric)** 100

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)