

Specification Sheet

Part Number: 156-03194

Bolt down one-piece design to bundle and secure two high voltage cables with convoluted tubing.

Compression limiter for high-torque bolted applications.

Integrated M6 Stud Mount acts as third hand for retention while attaching.

Releasable latch for serviceability.

Saddle with wide strap tie for third routing option



2-Pc P-Clamp, Dual Routing, M6 Mount, Assembled Wide Strap, 0.98" Max Dia., PA66HIRHSUV, Blk, 250/ctn

Article Number 156-03194

Type WSSDHVC24M6SD

Color Black (BK)

Quantity Per carton

Product Description These high voltage clamps replace expensive four-piece solutions consisting of a metal bracket, EPDM isolator, tie and stud retainer with a one-piece locking clamp. The hinged design snaps together to keep bundles separated and secures to any surface with a 6 mm stud or bolt. The wide strap option offers the possibility of a third routing.

Short Description	2-Pc P-Clamp, Dual Routing, M6 Mount, Assembled Wide Strap, 0.98" Max Dia., PA66HIRHSUV, Blk, 250/ctn
Global Part Name	WSSDHVC24M6SD-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	120
Minimum Tensile Strength (Metric)	535
Length L (Imperial)	4.48
Length L (Metric)	113.9
Fixation Method	Stud Mount
Identification Plate Position	none
Width W (Imperial)	1.20
Width W (Metric)	30.5
Bundle Diameter Max (Imperial)	0.98
Bundle Diameter Max (Metric)	25.0
Bundle Diameter 1st Loop Max (Imperial)	0.98
Bundle Diameter 1st Loop Max (Metric)	25.0
Bundle Diameter 2nd Loop Max (Imperial)	0.98
Bundle Diameter 2nd Loop Max (Metric)	25.0

Height H (Imperial)	1.24
Height H (Metric)	31.5
Mounting Hole Diameter D (Imperial)	0.24
Mounting Hole Diameter D (Metric)	M6 x 1
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	250
Package Quantity (Metric)	250
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)