

## Specification Sheet

Part Number: 156-03233



No drilling or extra hardware required – just secure to steel surface.

Magnetic mounts are reliable even in debris, dirt, and oil.

Use for permanent mounting or as a temporary installation tool.

Reuse and reposition capabilities allow for a flexible mounting solution.

Easily remove without residue.

2-Piece Cable Tie/Magnet Mount, Unassembled Set, 0.91" Dia, Magnet/POM/ST, 15lb Pull, Black, 100/Box

Article Number 156-03233

Type T50RMAGCTM15LSET

Color Black (BK)

Quantity Per box

**Product Description** Magnetic cable tie mount with T50R tie routes bundles by securing to steel surfaces without the need for a mounting hole. Simply attach the wire bundle to the mount with the cable tie and position it onto the beam, metal joist, ceiling channel, conveyor frame, or other steel surface. The mounts are simple to secure and can attach to surfaces contaminated with oil or debris. Ultra-strong neodymium magnets are ideal as a permanent mount or for temporary applications. Reuse and reposition them for ultimate flexibility without needing to replace or repurchase parts.

|                                     |  |
|-------------------------------------|--|
| Short Description                   | 2-Piece Cable Tie/Magnet Mount, Unassembled Set, 0.91" Dia, Magnet/POM/ST, 15lb Pull, Black, 100/Box |
| Global Part Name                    | T50RMAGCTM15LSET-NDFEB35M/POM/ST/PA66HS-BK   |
| Minimum Tensile Strength (Imperial) | 50   |
| Minimum Tensile Strength (Metric)   | 222  |
| Fixation Method                     | Magnet   |
| Identification Plate Position       | none   |
| Releasable Closure                  | No   |
| Tie Closure                         | plastic pawl   |
| Bundle Diameter Min (Imperial)      | 0.20   |
| Bundle Diameter Min (Metric)        | 5  |
| Bundle Diameter Max (Imperial)      | 1.97   |
| Bundle Diameter Max (Metric)        | 50   |
| Thickness T (Imperial)              | 0.047  |
| Thickness T (Metric)                | 1.2  |
| Height H (Imperial)                 | 0.41   |
| Height H (Metric)                   | 10.5   |

|                                |  |
|--------------------------------|--|
| Diameter D (Imperial)          | 0.91   |
| Diameter D (Metric)            | 23.2   |
| Cable Tie Width Max (Imperial) | 0.23   |
| Cable Tie Width Max (Metric)   | 5.9  |
| Material                       | Steel (ST) Polyacetal (POM) Polyamide 6.6 heat stabilized (PA66HS)<br>Neodymium alloy 35M (NDFEB35M) |
| Material Shortcut              | NDFEB35M ST POM PA66HS   |
| Material Cable Tie             | Polyamide 6.6 heat stabilized (PA66HS)   |
| Halogen Free                   | Yes  |
| Plenum Rating                  | AH-2   |
| Operating Temperature          | -40°F to +176°F (-40°C to +80°C)   |
| Reach Compliant (Article 33)   | Yes  |
| ROHS Compliant                 | Yes  |
| Package Quantity (Imperial)    | 100  |
| Package Quantity (Metric)      | 100  |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).