

Specification Sheet

Part Number: 156-03367



Pre-assembled 2-piece self-affixing tie with coupler
Cable tie head can be moved after bundling

Easy addition of cables after assembly

For parallel routing of bundles that can be twisted 90° even after installation

3-Piece T50R Tie with Coupler, 8" Long, 0.08 - 1.97" Dia, 50lbs, PA66HIRHS, Black, 500/bg

Article Number

156-03367

Type

T50RCOUPLER

Color

Black (BK)

Quantity Per

bag

Product Description

The Coupler is the simple way to connect two cable ties for a parallel routing of two bundles. His special design allows the ties 90 degrees of rotation. This is ideal for all applications where the cable, pipe or hose should move flexible in relation to the fixing point. The Coupler can be used with one or two cable ties. This allows easily subsequent installation or replacements of further cables, pipes or hose.

Short Description

3-Piece T50R Tie with Coupler, 8" Long, 0.08 - 1.97" Dia, 50lbs, PA66HIRHS, Black, 500/bg

Global Part Name T50RCOUPLER-PA66HIRHS/PA66HIR(S)-BK

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 225.0

Length L (Imperial) 7.874

Length L (Metric) 202.0

Identification Plate Position none

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.08

Bundle Diameter Min (Metric) 2.0

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 47.0

Bundle Diameter 1st Loop Max (Imperial) 1.97

Bundle Diameter 1st Loop Max (Metric) 50.0

Bundle Diameter 2nd Loop Max (Imperial) 1.97

Bundle Diameter 2nd Loop Max (Metric) 50.0

Height H (Imperial) 0.33

Height H (Metric) 8.3

Cable Tie Width Max (Imperial) 0.185

Cable Tie Width Max (Metric) 4.70

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Polyamide 6.6, high impact modified, scan black (PA66HIR(S))

Material Shortcut PA66HIRHS PA66HIR(S)

Material Cable Tie Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Flammability UL 94 HB

Operating Temperature -40°F to +230°F (-40°C to +110°C)

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).