

Specification Sheet

Part Number: 156-03950

Robust fir tree design provides low insertion effort yet delivers exceptional retention strength.

Anti-rotational oval fir tree keeps bundle in intended direction.

Standoff raises bundle 14.8 mm above mounting hole to protect it from rubbing, heat or obstructions.

Heavy duty T120 tie provides 120 lb (534 N) tensile strength to secure bundles up to 4" (104 mm).

Friction tab inside fir tree allows the tie to sit in mount without falling out prior to installation.



3-Piece Cable Tie/Oval Fir Tree Standoff Mount, Unassembled, 15"L, 12x17mm Hole, PA66HIRHSUV, Black, 500/ctn

Article Number 156-03950

Type T120R2xDHVSDOS12x17

Color Black (BK)

Quantity Per carton

Product Description HellermannTyton's fir tree mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an unassembled set.

Short Description	3-Piece Cable Tie/Oval Fir Tree Standoff Mount, Unassembled, 15"L, 12x17mm Hole, PA66HIRHSUV, Black, 500/ctn
Global Part Name	T120R2xDHVSDOS12x17-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	120
Minimum Tensile Strength (Metric)	535
Length L (Imperial)	8.0
Length L (Metric)	203.2
Fixation Method	Fir Tree for oval holes
Variant	Inside Serrated
Width W (Imperial)	1.26
Width W (Metric)	32
Bundle Diameter Min (Imperial)	0.20
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	4.13
Bundle Diameter Max (Metric)	105.0
Height H (Imperial)	1.24
Height H (Metric)	31.6

Cable Tie Width Max (Imperial)	0.30
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.19
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	4.73
Mounting Hole Diameter D (Imperial)	0.47 x 0.67
Mounting Hole Diameter D (Metric)	12.0 x 17.0 mm
Mounting Hole Diameter D Min (Imperial)	0.47 x 0.67
Mounting Hole Diameter D Max (Imperial)	0.47 x 0.67
Mounting Hole Diameter D Max (Metric)	17.4
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Flammability	UL 94 HB
Halogen Free	Yes

UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)