

Specification Sheet

Part Number: 156-03972

Made from 100% post-industrial recycled material, this product delivers the same elevated performance as our products made from standard impact-modified, heat-stabilized material.

The ReSource family of products helps companies meet their sustainability goals.

Assembly withstands vibrations and displacement forces.

Metal bushing accommodates high-torque tightening.



2-Piece Cable Tie/Screw Mount, Unassembled Set, 8" L, M6 Hole, 50lb, PA66HIRHS(REC100), Black, 1000/ctn

Article Number 156-03972

Type T50RCPCM67DTSSET

Color Black (BK)

Quantity Per carton

Product Description Part of our sustainable line of products, the ReSource product family features solutions made from excess plastic left over from the manufacturing process or from consumers. This cable tie mount is made from 100 percent postindustrial recycled plastic. It is secured with a mechanical fastener and includes an anti-rotation pin that keeps the mount and harness assembly in position while torquing the bolt or nut. It provides an attachment point for securing and routing a single bundle. The mount provides the highest level of fastening for critical cable security.

Short Description	2-Piece Cable Tie/Screw Mount, Unassembled Set, 8" L, M6 Hole, 50lb, PA66HIRHS(REC100), Black, 1000/ctn
Global Part Name	T50RCPCM67DTSSET-PA66HIRHS(REC100)-BK
Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.0
Length L (Metric)	202.0
Fixation Method	Screw Mount
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.79
Width W (Metric)	20.0
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.97

Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.061
Height H (Metric)	15.5
Stud Diameter (Metric)	6.0 mm
Stud Diameter (Imperial)	0.24
Material	Polyamide 6.6 recycled, high impact modified, heat stabilized (PA66HIRHS(REC100))
Material Shortcut	PA66HIRHS(REC100)
Flammability	UL 94 HB
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)