

## Specification Sheet

Part Number: 156-03972



This sustainable option in postindustrial recycled material offers the same performance level as our PA66HIRHS products.

The ReSource family of products helps companies meet their sustainability goals.

Assembly withstands vibrations and displacement forces.

Metal bushing accommodates high-torque tightening.

2-Piece Cable Tie/Screw Mount, Unassembled Set, 8" L, M6 Hole, 50lb, PA66HIRHS(REC100), Black, 1000/ctn

Article Number 156-03972

Type T50RCPCM67DTSSET

Color Black (BK)

Quantity Per carton

Product Description Part of our sustainable line of products, the ReSource product family features solutions made from excess plastic left over from the manufacturing process or from consumers. This cable tie mount is made from 100 percent postindustrial recycled plastic. It is secured with a mechanical fastener and includes an anti-rotation pin that keeps the mount and harness assembly in position while torquing the bolt or nut. It provides an attachment point for securing and routing a single bundle. The mount provides the highest level of fastening for critical cable security.

|                                     |   |
|-------------------------------------|---|
| Short Description                   | 2-Piece Cable Tie/Screw Mount, Unassembled Set, 8" L, M6 Hole, 50lb, PA66HIRHS(REC100), Black, 1000/ctn |
| Global Part Name                    | T50RCPCM67DTSSET-PA66HIRHS(REC100)-BK   |
| Minimum Tensile Strength (Imperial) | 50.0  |
| Minimum Tensile Strength (Metric)   | 225   |
| Length L (Imperial)                 | 8.0   |
| Length L (Metric)                   | 202.0   |
| Fixation Method                     | Screw Mount   |
| Identification Plate Position       | none  |
| Releasable Closure                  | No  |
| Tie Closure                         | plastic pawl  |
| Variant                             | Inside Serrated   |
| Width W (Imperial)                  | 0.79  |
| Width W (Metric)                    | 20.0  |
| Bundle Diameter Min (Imperial)      | 0.08  |
| Bundle Diameter Min (Metric)        | 2.0   |
| Bundle Diameter Max (Imperial)      | 1.97  |

|                              |   |
|------------------------------|---|
| Bundle Diameter Max (Metric) | 50.0  |
| Height H (Imperial)          | 0.061   |
| Height H (Metric)            | 15.5  |
| Stud Diameter (Metric)       | 6.0 mm  |
| Stud Diameter (Imperial)     | 0.24  |
| Material                     | Polyamide 6.6 recycled, high impact modified, heat stabilized (PA66HIRHS(REC100)) |
| Material Shortcut            | PA66HIRHS(REC100)   |
| Flammability                 | UL 94 HB  |
| Operating Temperature        | -40°F to +230°F (-40°C to +110°C)   |
| ROHS Compliant               | Yes   |
| Package Quantity (Imperial)  | 1000  |
| Package Quantity (Metric)    | 1000  |
| Customs Number               | 3926909988  |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)