

Specification Sheet

Part Number: 156-04032

Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.

Initial fir tree serves as a locating feature for assistance in blind assembly applications.

Product Image

Disc feature provides anti-rattle protection in high vibration applications.

2-Pc Cable Tie/Fir Tree Mount, 8.0"L, 0.38 - 0.39" Mounting Hole, 50lb, PA66/PA66HIRHS, Orange/Black, 500/pkg

Article Number

156-04032

Type

T50RFT10

Color

Black (BK) Orange (OG), High Voltage (HV)

Quantity Per

bag

Product Description

Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.

Short Description

2-Pc Cable Tie/Fir Tree Mount, 8.0"L, 0.38 - 0.39" Mounting Hole, 50lb, PA66/PA66HIRHS, Orange/Black, 500/pkg

Global Part Name

T50RFT10-PA66HIRHS/PA66-OG/BK

Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	8.0
Length L (Metric)	203.2
Fixation Method	Fir Tree
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.20
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.05
Height H (Metric)	1.2

Panel Thickness Min (Imperial)	0.024
Panel Thickness Max (Imperial)	0.197
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	5.0
Mounting Hole Diameter D (Imperial)	0.38 - 0.39
Mounting Hole Diameter D (Metric)	9.7 - 10.0 mm
Mounting Hole Diameter D Min (Imperial)	0.38
Mounting Hole Diameter D Max (Imperial)	0.39
Mounting Hole Diameter D Max (Metric)	10.0
Disc Diameter (Metric)	18.0
Disc Diameter (Imperial)	0.71
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 (PA66)
Material Shortcut	PA66 PA66HIRHS
Flammability	UL 94 V-2
ROHS Compliant	Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500