

Specification Sheet

Part Number: 156-04041

Versatile design allows cable routing above, perpendicular or parallel to stud.

Can mount up to three bundles simultaneously, making efficient use of a single mounting point.

Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.



2-Piece M5/T5/M6/T6 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HS/PA66HIRHS, Orange/Black, 3000/pkg

Article Number 156-04041

Type T50ROSBS5-6U-SET

Color Black (BK) Orange (OG), High Voltage (HV)

Quantity Per carton

Product Description Unique, two-piece design allows routing to be above, parallel or perpendicular to stud. This also enables up to three separate bundles to be fastened to the same stud. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.

Short Description	2-Piece M5/T5/M6/T6 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HS/PA66HIRHS, Orange/Black, 3000/pkg
Global Part Name	T50ROSBS5-6U-SET-PA66HIRHS-OG/BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	222.0
Length L (Imperial)	8.0
Length L (Metric)	203.2
Fixation Method	Weld Stud Fixing
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.92
Width W (Metric)	23.25
Bundle Diameter Min (Imperial)	0.16
Bundle Diameter Min (Metric)	4.0
Bundle Diameter Max (Imperial)	1.97

Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.74
Height H (Metric)	18.75
Mounting Hole Diameter D (Imperial)	0.20" x 0.03"; 0.24" x 0.04"; 0.20
Mounting Hole Diameter D (Metric)	M5 x 0.8 T5 M6 x 1
Stud Diameter (Metric)	6.0 mm 5.0 mm
Stud Diameter (Imperial)	0.20 ", 0.24
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	3000

Package Quantity (Metric)

3000

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)