

Specification Sheet

Part Number: 156-04042



Design gives quick and easy assembly by hand without the need for tools.

Mount can be used in a wide variety of applications where 8mm weld studs or 8mm ISO bolts.

Design provides low insertion force and high extraction force.

2-Piece M8 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HIRHS/PA66HIRHSUV, Orange/Black, 2000/pkg

Article Number	156-04042
Type	T50ROSB8SET
Color	Black (BK) Orange (OG), High Voltage (HV)
Quantity Per	carton
Product Description	The flexibility of the two-piece stud mount allows cables to route parallel to, perpendicular to or right over a stud. The three-saddle design on these single stud mounts can also accommodate up to three routings. Parts listed below are for the single routing but additional ties can be used to route more than one bundle on the mount.
Short Description	2-Piece M8 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HIRHS/PA66HIRHSUV, Orange/Black, 2000/pkg
Global Part Name	T50ROSB8SET-PA66HIRHS/PA66HIRHSUV-OG/BK

Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	7.95
Length L (Metric)	202.0
Fixation Method	Stud Mount
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.16
Bundle Diameter Min (Metric)	4.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.98
Height H (Metric)	25.0

Cable Tie Width Max (Imperial)	0.21
Mounting Hole Diameter D (Imperial)	0.31 x 0.04
Stud Diameter (Metric)	8.0 mm
Stud Diameter (Imperial)	0.31
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Foot Part Material	PA66HIRHSUV
Material Shortcut	PA66HIRHSUV PA66HIRHS
Material Cable Tie	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes

Package Quantity (Imperial) 2000

Package Quantity (Metric) 2000

Customs Number 3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)