

## Specification Sheet

Part Number: 156-04054

Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.

Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

Two piece assembly allows the mount to slide along the strap ensuring proper orientation.

Cable tie is outside serrated to reduce bundle chafing.



2-Piece Cable Tie & Edge Clip, 8.0"L, EC23, 3 - 6 mm Panel, 50lb, PA66HIRHS/PA66HIRHSUV, OG/BK,500/pkg

|                     |  |
|---------------------|--|
| Article Number      | 156-04054  |
| Type                | T50REC24   |
| Color               | Black (BK) Orange (OG), High Voltage (HV)  |
| Quantity Per        | bag  |
| Product Description | HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge slip in place. |
| Short Description   | 2-Piece Cable Tie & Edge Clip, 8.0"L, EC23, 3 - 6 mm Panel, 50lb, PA66HIRHS/PA66HIRHSUV, OG/BK,500/pkg   |

|                                     |  |
|-------------------------------------|--|
| Global Part Name                    | T50REC24-PA66HIRHS-OG/BK               |
| Minimum Tensile Strength (Imperial) | 50.0                                   |
| Minimum Tensile Strength (Metric)   | 225.0                                  |
| Length L (Imperial)                 | 8.0                                    |
| Length L (Metric)                   | 200.0                                  |
| Fixation Method                     | EdgeClip, sideways, assembled, 2 piece |
| Identification Plate Position       | none                                   |
| Variant                             | Inside Serrated                        |
| Width W (Imperial)                  | 0.18                                   |
| Width W (Metric)                    | 4.6                                    |
| Bundle Diameter Min (Imperial)      | 0.04                                   |
| Bundle Diameter Min (Metric)        | 1.0                                    |
| Bundle Diameter Max (Imperial)      | 1.77                                   |
| Bundle Diameter Max (Metric)        | 45.0                                   |
| Height H (Imperial)                 | 0.05                                   |
| Height H (Metric)                   | 1.2                                    |

|                                |  |
|--------------------------------|--|
| Panel Thickness Min (Imperial) | 0.12   |
| Panel Thickness Max (Imperial) | 0.24   |
| Panel Thickness Min (Metric)   | 3.0  |
| Panel Thickness Max (Metric)   | 6.0  |
| Material                       | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut              | PA66HIRHS  |
| Material Cable Tie             | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Operating Temperature          | -40°F to +221°F (-40°C to +105°C)                                |
| ROHS Compliant                 | Yes  |
| Package Quantity (Imperial)    | 500  |
| Package Quantity (Metric)      | 500  |