

Specification Sheet

Part Number: 156-04062

Pre-assembled 2-piece self-affixing tie with coupler
Cable tie head can be moved after bundling

Easy addition of cables after assembly

For parallel routing of bundles that can be twisted 90° even after installation



3-Pc T50R Tie with Coupler, 8" Long, 0.08" - 1.97" Dia, 50lbs, PA66HIRHS/PA66HIRHSUV, Orange/Black, 1000/ctn

Article Number	156-04062
Type	T50RCOUPLER
Color	Black (BK) Orange (OG), High Voltage (HV)
Quantity Per	carton
Product Description	The Coupler is the simple way to connect two cable ties for a parallel routing of two bundles. His special design allows the ties 90 degrees of rotation. This is ideal for all applications where the cable, pipe or hose should move flexible in relation to the fixing point. The Coupler can be used with one or two cable ties. This allows easily subsequent installation or replacements of further cables, pipes or hose.
Short Description	3-Pc T50R Tie with Coupler, 8" Long, 0.08" - 1.97" Dia, 50lbs, PA66HIRHS/PA66HIRHSUV, Orange/Black, 1000/ctn

Global Part Name

T50RCOUPLER-PA66HIRHS/PA66HIRHSUV-OG/BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225.0

Length L (Imperial)

7.874

Length L (Metric)

202.0

Identification Plate Position

none

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.18

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.08

Bundle Diameter Min (Metric)

2.0

Bundle Diameter Max (Imperial)

1.97

Bundle Diameter Max (Metric)

47.0

Bundle Diameter 1st Loop Max (Imperial)

1.97

Bundle Diameter 1st Loop Max (Metric)

50.0

Bundle Diameter 2nd Loop Max (Imperial) 1.97

Bundle Diameter 2nd Loop Max (Metric) 50.0

Cable Tie Width Max (Imperial) 0.185

Cable Tie Width Max (Metric) 4.70

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Polyamide 6.6 high impact modified, heat and UV stabilized
(PA66HIRHSUV)

Material Shortcut PA66HIRHSUV PA66HIRHS

ROHS Compliant Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000