

Specification Sheet

Part Number: 156-04083


Pre-assembled 2-piece fixing tie with fir tree foot part.
Cable tie head can be moved after bundling.

Easy to assemble without the need for a tool.

Disc adjusts tie for pressure from various directions and minimises access of dust and dirt.

Fir tree foot part can be used for a variety of panel thicknesses.

Suitable for use within threaded holes.



2-Pc Cable Tie/Fir Tree Mount, 8.0"L, 6.1-7.0mm Mounting Hole Dia, PA66HIRHSUV, BK, 1000/CTN

Article Number 156-04083

Type T50RX2DUALSDFT6.5A

Color Black (BK)

Quantity Per carton

Product Description These three-piece self-affixing cable ties are supplied ready assembled and offer a simple and versatile method of bundling and fastening cables. The deep-hole anchor will easily push into blind holes with or without thread and offers a very secure attachment. The two-piece design enables the head of the tie to be oriented to the required position to ease assembly, while the disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Short Description	2-Pc Cable Tie/Fir Tree Mount, 8.0"L, 6.1-7.0mm Mounting Hole Dia, PA66HIRHSUV, BK, 1000/CTN
Global Part Name	T50RX2DUALSDFT6.5A-PA66HIRHSUV-BK
Length L (Imperial)	1.81
Length L (Metric)	46
Fixation Method	Fir Tree
Identification Plate Position	none
Tie Closure	plastic pawl
Width W (Imperial)	0.46
Width W (Metric)	11.7
Bundle Diameter Min (Imperial)	0.6
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.9
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.80
Height H (Metric)	20.5

Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.23
Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.1 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.27
Mounting Hole Diameter D Max (Metric)	7.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Flammability	UL 94 HB
Halogen Free	Yes

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000