

Specification Sheet

Part Number: 156-04197

One-piece ratchet clamp can be pre-installed on the torque tube, even prior to arrival of modules and wire harnesses onsite.

Quick, toolless, one-handed installation is easier and safer for installers.

Releasable and re-closeable clamp allows for adjusting or adding wires.

Plastic construction won't cut or chafe wires.

Clamp saddle provides additional routing option using a cable tie, eliminating the need to drill or add complex routing parts.

Impact modified, heat and UV stabilized PA66 provides long-term durability in extreme environments.

ATI-specific stainless steel mounting clip designed to last through severe weather and single axis tracker movement.



ATI Ratchet Clamp, 0.76 - 1.42" Bundle Dia, PA66HIRHSUV/SS, Black, 200/ctn

Article Number 156-04197

Type IRCCATI

Color Black (BK)

Quantity Per box

Product Description	The ATI (Array Technologies) Ratchet Clamp attaches to Array Technologies torque tubes without any additional hardware. It offers one-handed, toolless simplicity and size versatility for managing wires and cables on solar modules. The robust design and solar-optimized materials make it ideal for heavy duty, outdoor applications. The one-piece adjustable clamp can be closed by hand to the desired diameter, replacing multiple sizes for single-diameter fasteners. The integrated release feature enables easy and nondestructive removal of cables by inserting a flat-head screwdriver. This allows the clamp to be reused without removing it.
Short Description	ATI Ratchet Clamp, 0.76 - 1.42" Bundle Dia, PA66HIRHSUV/SS, Black, 200/ctn
Global Part Name	IRCCATI-PA66HIRHSUV/SS304-BK
Length L (Imperial)	4.56
Length L (Metric)	115.9
Fixation Method	Mounting Hanger
Releasable Closure	Yes
Width W (Imperial)	1.37
Width W (Metric)	34.8
Bundle Diameter Min (Imperial)	0.76
Bundle Diameter Min (Metric)	19.3
Bundle Diameter Max (Imperial)	1.42
Bundle Diameter Max (Metric)	36.1

Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV SS304
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	200
Package Quantity (Metric)	200
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)