

Specification Sheet

Part Number: 157-00040



Oval mount design pushes on easy by hand without the need for tools. Design provides low insertion and high extraction force.

1-Pc Cable Tie/Oval Stud Mount, 6.0" Long, PA66HS, Black, 500/pkg

Article Number 157-00040

Type T50SOSSBD-M10

Color Black (BK)

Quantity Per bag

Product Description The special oval shape provides for an approximate lateral adjustment, allowing for any misalignment of the stud or incorrect positioning of the tie on the cables

Short Description 1-Pc Cable Tie/Oval Stud Mount, 6.0" Long, PA66HS, Black, 500/pkg

Global Part Name T50SOSSBD-M10-PA66HSUV-BK

| | |
|--|------------------|
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 150 |
| Length L (Imperial) | 7.0 |
| Length L (Metric) | 175.0 |
| Fixation Method | Weld Stud Fixing |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Outside Serrated |
| Width W (Imperial) | 0.22 |
| Width W (Metric) | 5.7 |
| Bundle Diameter Min (Imperial) | 0.12 |
| Bundle Diameter Min (Metric) | 3.0 |
| Bundle Diameter Max (Imperial) | 1.2 |
| Bundle Diameter Max (Metric) | 30.0 |
| Thickness T (Metric) | 1.3 |
| Stud Diameter (Metric) | M10 |

| | |
|-------------------------------------|--|
| Material | Polyamide 6.6 heat and UV-resistant (PA66HSUV) |
| Material Shortcut | PA66HSUV |
| Material Cable Tie | Polyamide 6.6 heat and UV-resistant (PA66HSUV) |
| Flammability | UL 94 V2 |
| Operating Temperature | -40°F to +230°F (-40°C to +110°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |