

## Specification Sheet

Part Number: 157-00060



Stand Off Dual Clamp Tie, 26.10" Long, .31" Stud Dia, PA66HIRHSUV, Black, 250/pkg

<b>Article Number</b>	157-00060
<b>Type</b>	SDCTL
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Wide strap minimizes pinching of soft hoses and convoluted tubing.</li><li>• Clamping rails increase circumferential grip on varying bundle diameters.</li><li>• Locking stud mount pawls allow for easy hand insertion.</li><li>• Nut or weld nesting counterbore provides flush mounting at the base.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	Stand Off Dual Clamp Ties offer the same features as the standard dual clamp tie, with a standoff mount that secures the bundle away from the side of the frame rail. This protects the bundles from bolts and other protrusions.
<b>Short Description</b>	Stand Off Dual Clamp Tie, 26.10" Long, .31" Stud Dia, PA66HIRHSUV, Black, 250/pkg

Global Part Name

SDCTL-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

100.0

Minimum Tensile Strength (Metric)

445.0

Length L (Imperial)

26.1

Length L (Metric)

663.0

Fixation Method

Weld Stud Fixing

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Width W (Imperial)

0.5

Width W (Metric)

12.7

Bundle Diameter Min (Imperial)

0.375

Bundle Diameter Min (Metric)

9.5

Bundle Diameter Max (Imperial)

3.4

Bundle Diameter Max (Metric)

86.4

Height H (Imperial)

1.47

Height H (Metric)

37.30

<b>Stud Diameter (Metric)</b>	M8
<b>Stud Diameter (Imperial)</b>	5/16
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	250
<b>Package Quantity (Metric)</b>	250
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	bag