

## Specification Sheet

Part Number: 157-00105



Head allows for a .2" lateral adjustment on stud during installation.  
Quick and easy installation ideal for manufacturing environment.

1-Pc Cable Tie/Oval Stud Mount, 6.6" Long, 50lb Tensile, With Thumb Bar, PA66HS, Black, 3000/pkg

<b>Article Number</b>	157-00105
<b>Type</b>	T50SOSSB5-High-E-C-CC
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	bag
<b>Product Description</b>	Oval Shaped Stud Mount's special design allows for a .20" (5.5 mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The mount allows it to be installed onto a weld stud without the use of any tools.
<b>Short Description</b>	1-Pc Cable Tie/Oval Stud Mount, 6.6" Long, 50lb Tensile, With Thumb Bar, PA66HS, Black, 3000/pkg
<b>Global Part Name</b>	T50SOSSB5-High-E-C-CC-PA66HS-BK

<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225.0
<b>Length L (Imperial)</b>	6.6
<b>Length L (Metric)</b>	167.0
<b>Fixation Method</b>	Weld Stud Fixing
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Outside Serrated
<b>Width W (Imperial)</b>	0.2
<b>Width W (Metric)</b>	5.0
<b>Bundle Diameter Min (Imperial)</b>	0.04
<b>Bundle Diameter Min (Metric)</b>	1.0
<b>Bundle Diameter Max (Imperial)</b>	1.38
<b>Bundle Diameter Max (Metric)</b>	35.0
<b>Stud Length Max (Imperial)</b>	0.56

<b>Stud Length Max (Metric)</b>	14.2
<b>Stud Diameter (Metric)</b>	5.0 mm
<b>Stud Diameter (Imperial)</b>	0.20
<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature</b>	-40°F to +257°F (-40°C to +125°C)
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	3000
<b>Package Quantity (Metric)</b>	3000
<b>Customs Number</b>	3926909988