

Specification Sheet

Part Number: 157-00132



Offset Fir Tree, 8.5" Long, 50lb Tensile Strength, PA66HIRHS, Black, 500/pkg

Article Number

157-00132

Type

T50ROSFT6SO12.5B

Color

Black (BK)

Features & Benefits

- An all-in-one bundling and fixing solution reduces costs.
- High-specification materials and superior design suit the fixing and bundling needs of complex applications.

Quantity Per

bag

Product Description

The Offset Cable Ties route and position wire and cable bundles away from a mounting hole. The offset bar between the fir tree and cable tie strap provides a robust and cored-out design to eliminate any potential bending of the wire or cable assembly once installed. The combination of 12.5mm and 25mm offset distances and various fir tree sizes offer coverage for a majority of industry offset routing application. The outside serrations of the tie strap present a smooth surface to the cables preventing any possible damage to soft or delicate bundles. One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description

Offset Fir Tree, 8.5" Long, 50lb Tensile Strength, PA66HIRHS, Black, 500/pkg

Global Part Name

T50ROSFT6SO12.5B-PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

222

Length L (Imperial)

8.5

Length L (Metric)

215.9

Offset Length(Imperial)

0.49

Offset Length(Metric)

12.5

Identification Plate Position

none

Releasable Closure

No

Width W (Imperial)

0.19

Width W (Metric)

5.1

Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	1.6
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.90
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.26
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.65
Mounting Hole Diameter D (Imperial)	0.24 - 0.28 ";0.24 - 0.26
Mounting Hole Diameter D (Metric)	6.1 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.28 ";0.26
Mounting Hole Diameter D Max (Metric)	7.0
Disc Diameter(Metric)	15.0
Disc Diameter (Imperial)	0.59

Material

Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut

PA66HIRHS

Material Cable Tie

Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

ROHS Complaint

Yes

Package Quantity(Imperial)

500

Package Quantity (Metric)

500