

Specification Sheet

Part Number: 157-00140



1-Piece Cable Tie/Fir Tree Mount with Disc, 6.7"L, .24"-.27" Mounting Hole, PA66HIRHS, Black, 500/pkg

Article Number

157-00140

Type

T50SOSFT6LG-E2

Color

Black (BK)

Features & Benefits

- Off-Set design allows bundles to sit off of mounting points to avoid friction against surrounding areas.
- Fir tree gives 3 to 1 extraction versus insertion force making them strong and easy to install.
- Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.

Quantity Per

bag

Product Description

HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Short Description	1-Piece Cable Tie/Fir Tree Mount with Disc, 6.7"L, .24"-.27" Mounting Hole, PA66HIRHS, Black, 500/pkg
Global Part Name	T50SOSFT6LG-E2-PA66HIRHS-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	180
Length L (Imperial)	6.7
Length L (Metric)	167.0
Fixation Method	Fir Tree
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.04
Bundle Diameter Min (Metric)	1.0
Bundle Diameter Max (Imperial)	1.4
Bundle Diameter Max (Metric)	35.0

Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3
Height H (Imperial)	.60
Height H (Metric)	16.10
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.3
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	8.25
Mounting Hole Diameter D (Imperial)	0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.27
Mounting Hole Diameter D Max (Metric)	6.9
Disc Diameter(Metric)	16.0
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut

PA66HIRHS

Flammability

UL 94 V2

Operating Temperature (Metric)

-40°F to +221°F (-40°C to +105°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

500

Package Quantity (Metric)

500

Customs Number

3926909987

Content Unit(BMEcat)

pcs.