

Specification Sheet

Part Number: 157-00144



1-Piece Cable Tie/Fir Tree Mount with Disc, 8"L, PA46, Brown, 500/pkg

Article Number	157-00144
Type	T50ROSFTQM6
Color	Brown (BN)
Features & Benefits	<ul style="list-style-type: none">• One-piece design allows installers to mount and bundle wire or cables single-handedly.• Fastener delivers high extraction force for reliable performance, yet it's easy to install.• Can be unscrewed or extracted from threaded holes for easy removal and re-usability.
Quantity Per	bag

Product Description

HellermannTyton Blind Hole Mount Cable Tie for threaded holes offers an easy-to-use method for bundling and affixing cables. The one-piece mount offers a low insertion force and aggressively resists pull off, for secure attachment to panel holes with thicknesses from 0.02" to 0.28" or threaded blind holes. The disc on top of the mount covers the hole and minimizes ingress of water and debris.

Short Description	1-Piece Cable Tie/Fir Tree Mount with Disc, 8"L, PA46, Brown, 500/pkg
Global Part Name	T50ROSFTQM6-PA46-BN
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	222
Length L (Imperial)	8.0
Length L (Metric)	203.6
Fixation Method	Fir Tree
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.2
Width W (Metric)	5.08
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.6
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Thickness T (Imperial)	0.06

Thickness T (Metric) 1.5

Height H (Imperial) 0.54

Height H (Metric) 13.8

Diameter D (imperial) 0.25

Diameter D (metric) 6.0

Panel Thickness Min(Imperial) 0.02

Panel Thickness Max(Imperial) 0.28

Panel Thickness Min (Metric) 0.6

Panel Thickness Max (Metric) 7.0

Mounting Hole Diameter D (Imperial) 0.24

Mounting Hole Diameter D (Metric) M6

Mounting Hole Diameter D Min (Imperial) 0.24

Mounting Hole Diameter D Max (Imperial) 0.24

Mounting Hole Diameter D Max (Metric) 6.0

Disc Diameter(Metric) 15.88

Disc Diameter (Imperial) 0.66

Material	Polyamide 4.6 (PA46)
Material Shortcut	PA46
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +275°F (-40°C to +135°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909987
Content Unit(BMEcat)	pcs.