

Specification Sheet

Part Number: 157-00152



1-Piece Cable Tie/Fir Tree Mount, 6.5mm hole dia., 0.6-8.25mm Panel Thickness, PA66HIRHS, Gray, 1,000/bag

Article Number

157-00152

Type

T50SOSFT6LG-E2

Color

Gray (GY)

Features & Benefits

- Off-Set design allows bundles to sit off of mounting points to avoid friction against surrounding areas.
- Fir tree gives 3 to 1 extraction versus insertion force making them strong and easy to install.
- Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.

Quantity Per

box

Product Description

HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Short Description

1-Piece Cable Tie/Fir Tree Mount, 6.5mm hole dia., 0.6-8.25mm Panel Thickness, PA66HIRHS, Gray, 1,000/bag

Global Part Name

T50SOSFT6LG-E2-PA66HS-GY

Minimum Tensile Strength (Imperial)

40.47

Minimum Tensile Strength (Metric)

180

Length L (Imperial)

6.57

Length L (Metric)

167.0

Fixation Method

Fir Tree

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Width W (Imperial)

0.181

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.04

Bundle Diameter Min (Metric)

1.0

Bundle Diameter Max (Imperial)

1.38

Bundle Diameter Max (Metric)

35.0

Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.325
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	8.25
Mounting Hole Diameter D (Imperial)	0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.27
Mounting Hole Diameter D Max (Metric)	6.9
Disc Diameter(Metric)	16.0
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 HB

Operating Temperature (Metric)

-40°F to +221°F (-40°C to +105°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

5000

Package Quantity (Metric)

5000

Customs Number

3926909988

Content Unit(BMEcat)

pcs.