

Specification Sheet

Part Number: 157-00164



1-Piece Cable Tie/Offset Fir Tree with Disc, 25 mm Offset/90° Angle, 9.4"L, 6.1–7mm Hole, PA66HIRHS, BK, 500/pkg

Article Number

157-00164

Type

T50ROSFT6SO25R

Color

Black (BK)

Features & Benefits

- All-in-one bundling and fastening solution reduces costs and assembly time.
- Variety of fir tree diameters and offset lengths address most offset applications.
- High-spec materials and superior design deliver excellent performance and value.

Quantity Per

box

Product Description

Offset cable ties route and position bundles away from a mounting hole. Rigid offset bar eliminates potential bending of wire or cables once installed. Multiple offset distances and fir tree sizes cover the majority of industry offset applications. The tie strap's outside serration design provides a smooth surface to protect soft bundles. HellermannTyton's one-piece mounting ties offer a complete solution by both bundling and mounting. Their ideal combination of high-specification materials and superior design suit the needs of complex applications.

Short Description

1-Piece Cable Tie/Offset Fir Tree with Disc, 25 mm Offset/90° Angle, 9.4"L, 6.1–7mm Hole, PA66HIRHS, BK, 500/pkg

Global Part Name

T50ROSFT6SQ25R-PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

222.0

Length L (Imperial)

9.4

Length L (Metric)

237.7

Offset Length(Imperial)

0.98

Offset Length(Metric)

25.0

Fixation Method

Fir Tree

Identification Plate Position

none

Releasable Closure

No

Width W (Imperial)

0.20

Width W (Metric)

5.1

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.5

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

Height H (Imperial) 0.97

Height H (Metric) 15.10

Panel Thickness Min(Imperial) 0.02

Panel Thickness Max(Imperial) 0.32

Panel Thickness Min (Metric) 0.60

Panel Thickness Max (Metric) 8.25

Mounting Hole Diameter D (Imperial) 0.24 - 0.28

Mounting Hole Diameter D (Metric) 6.1 - 7.0 mm

Mounting Hole Diameter D Min (Imperial) 0.24

Mounting Hole Diameter D Max (Imperial) 0.28

Mounting Hole Diameter D Max (Metric) 7.0

Disc Diameter(Metric) 19.0

Disc Diameter (Imperial) 0.75

Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Material Cable Tie	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988
Content Unit(BMEcat)	pcs.