


Specification Sheet

Part Number: 157-00167



1-Pc Cable Tie/Fir Tree Mount, 25mm Offset, 9.1"L, FT6 Hole, 50lb, PA66HIRHS, Gray, 500/pkg

Article Number	157-00167
Type	T50ROSFT5SO25A
Color	Gray (GY)
Features & Benefits	<ul style="list-style-type: none">• One-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables, through the design of the fir tree by ensuring positive and secure fixing into panels with thicknesses from 0.6-6.65mm.• The offset on the cable tie creates an alternate solution when an offset fixing option is required and a tape clip cannot be used due to the design which reduces the potential of the bundle flexing or shifting.• The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.
Quantity Per	carton

Product Description

HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Short Description

1-Pc Cable Tie/Fir Tree Mount, 25mm Offset, 9.1"L, FT6 Hole, 50lb, PA66HIRHS, Gray, 500/pkg

Global Part Name

T50ROSFT5SO25A-PA66HIRHS-GY

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225.0

Length L (Imperial)

9.1

Length L (Metric)

230.0

Offset Length(Imperial)

0.98

Offset Length(Metric)

25.0

Identification Plate Position

none

Releasable Closure

No

Width W (Imperial)

0.20

Width W (Metric)

5.1

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.5

Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.84
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.20
Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	5.10
Mounting Hole Diameter D (Imperial)	0.19 - 0.20
Mounting Hole Diameter D (Metric)	4.8 - 5.2 mm
Mounting Hole Diameter D Min (Imperial)	0.19
Mounting Hole Diameter D Max (Imperial)	0.20
Mounting Hole Diameter D Max (Metric)	5.2
Disc Diameter (Imperial)	0.75
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)

ROHS Complaint

Yes

Package Quantity(Imperial)

500

Package Quantity (Metric)

500

Customs Number

3926909988