

Specification Sheet

Part Number: 157-00231



Rotated Offset Cable Ties with Fir Tree secures and fastens bundles away from obstructions, heat or sources of abrasion.

All-in-one bundling and fastening solution reduces costs and assembly time.

Variety of fir tree diameters and offset lengths address most offset applications.

Versatile high performance fir tree design demonstrates easy insertion with high extraction resistance.

1-Piece Cable Tie/Fir Tree Mount with Disc, 9.3"L, M10, 0.31" Hole, PA66HIRHSUV, Black, 3000/ctn

| | |
|----------------|-------------------|
| Article Number | 157-00231 |
| Type | T50ROSFT8M10SO25R |
| Color | Black (BK) |
| Quantity Per | carton |

| | |
|-------------------------------------|---|
| Product Description | Offset cable ties route and position bundles away from a mounting hole. Rigid offset bar eliminates potential bending of wire or cables once installed. Multiple offset distances and fir tree sizes cover the majority of industry offset applications. The tie strap's outside serration design provides a smooth surface to protect soft bundles. HellermannTyton's one-piece mounting ties offer a complete solution by both bundling and mounting. Their ideal combination of high-specification materials and superior design suit the needs of complex applications. |
| Short Description | 1-Piece Cable Tie/Fir Tree Mount with Disc, 9.3"L, M10, 0.31" Hole, PA66HIRHSUV, Black, 3000/ctn |
| Global Part Name | T50ROSFT8M10SO25R-PA66HIRHSUV-BK |
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 225.0 |
| Length L (Imperial) | 9.37 |
| Length L (Metric) | 238.0 |
| Offset Length (Imperial) | 0.98 |
| Offset Length (Metric) | 25.0 |
| Fixation Method | Fir tree for round holes |
| Identification Plate Position | none |
| Releasable Closure | No |
| Variant | Outside Serrated |

| | |
|---|--------------|
| Width W (Imperial) | 0.02 |
| Width W (Metric) | 5.08 |
| Bundle Diameter Min (Imperial) | 0.08 |
| Bundle Diameter Min (Metric) | 2.0 |
| Bundle Diameter Max (Imperial) | 1.97 |
| Bundle Diameter Max (Metric) | 50.0 |
| Height H (Imperial) | 0.23 |
| Height H (Metric) | 5.8 |
| Panel Thickness Min (Imperial) | 0.02 |
| Panel Thickness Max (Imperial) | 0.21 |
| Panel Thickness Min (Metric) | 0.60 |
| Panel Thickness Max (Metric) | 5.5 |
| Mounting Hole Diameter D (Imperial) | 0.30 - 0.33 |
| Mounting Hole Diameter D (Metric) | 7.6 - 8.4 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.30 |
| Mounting Hole Diameter D Max (Imperial) | 0.33 |
| Mounting Hole Diameter D Max (Metric) | 8.4 |

| | |
|-----------------------------|--|
| Disc Diameter (Metric) | 19.0 |
| Disc Diameter (Imperial) | 0.75 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| Halogen Free | Yes |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 3000 |
| Package Quantity (Metric) | 3000 |