

Specification Sheet

Part Number: 157-00302



1-Pc Cable Tie/Fir Tree Mount with Disc, 6.5"L, 6.3 - 7.0 mm Hole Dia, PA66HIRHSUV, Black, 4000/pkg

Article Number 157-00302

Type T50SOSFT6.5LG-E4X

Color Black (BK)

Features & Benefits

- All-in-one bundling and fastening solution reduces costs and assembly time.
- Disc feature provides anti-rattle protection in high-vibration applications.

Quantity Per carton

Product Description	One-piece mounting ties offer a complete solution by both bundling and mounting wires, cables and tubes. The fir tree mount provides low insertion force with a high extraction force. Outside serrations on the cable tie leave a smooth interior surface that's gentler on sensitive wire insulation. The unique head design allows the cable tie to firmly hold bundles as small as .06" diameter. The disc offers added protection against debris.
Short Description	1-Pc Cable Tie/Fir Tree Mount with Disc, 6.5"L, 6.3 - 7.0 mm Hole Dia, PA66HIRHSUV, Black, 4000/pkg
Global Part Name	T50SOSFT6.5LG-E4X-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	6.5
Length L (Metric)	165.0
Fixation Method	Fir Tree
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.18

Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.04
Bundle Diameter Min (Metric)	1.0
Bundle Diameter Max (Imperial)	1.38
Bundle Diameter Max (Metric)	35.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3
Panel Thickness Min(Imperial)	0.03
Panel Thickness Max(Imperial)	0.28
Panel Thickness Min (Metric)	0.7
Panel Thickness Max (Metric)	7.0
Mounting Hole Diameter D (Imperial)	0.25 - 0.28
Mounting Hole Diameter D (Metric)	6.3 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0
Disc Diameter(Metric)	16.0

Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
ROHS Complaint	Yes
Use Conditions	For Indoor and Outdoor Use
Package Quantity(Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988
Content Unit(BMEcat)	pcs.
Weight (Metric)	0.001
Weight (Imperial)	0.003

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)