

## Specification Sheet

Part Number: 157-00330



1-Pc Cable Tie/Fir Tree Mount w/Disc, 12.5mm Offset, 8.5"L, 6.1-7mm Hole; PA66HIRHS, Gray, 2000/ctn

<b>Article Number</b>	157-00330
<b>Type</b>	T50ROSFT6SO12.5A
<b>Color</b>	Gray (GY)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Off-Set design allows bundles to sit off of mounting points to avoid friction against surrounding areas.</li><li>• Fir tree gives 3 to 1 extraction versus insertion force making them strong and easy to install.</li><li>• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

**Short Description**

1-Pc Cable Tie/Fir Tree Mount w/Disc, 12.5mm Offset, 8.5"L, 6.1-7mm Hole; PA66HIRHS, Gray, 2000/ctn

**Global Part Name**

T50ROSFT6SO12.5A-PA66HIRHS-GY

**Minimum Tensile Strength (Imperial)**

50.0

**Minimum Tensile Strength (Metric)**

225

**Length L (Imperial)**

8.5

**Length L (Metric)**

215.5

**Offset Length(Imperial)**

0.49

**Offset Length(Metric)**

12.5

**Identification Plate Position**

none

**Releasable Closure**

No

**Width W (Imperial)**

0.19

**Width W (Metric)**

5.1

**Bundle Diameter Min (Imperial)**

0.08

**Bundle Diameter Min (Metric)**

1.6

**Bundle Diameter Max (Imperial)**

1.97

**Bundle Diameter Max (Metric)**

50.0

<b>Thickness T (Metric)</b>	1.4
<b>Height H (Imperial)</b>	0.87
<b>Panel Thickness Min(Imperial)</b>	0.02
<b>Panel Thickness Max(Imperial)</b>	0.26
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	6.65
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 - 0.28 ";0.24 - 0.26
<b>Mounting Hole Diameter D (Metric)</b>	6.5 mm 6.35 mm (hexagonal)
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.28 ";0.26
<b>Mounting Hole Diameter D Max (Metric)</b>	7.0
<b>Disc Diameter(Metric)</b>	15.0
<b>Disc Diameter (Imperial)</b>	0.59
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>ROHS Complaint</b>	Yes

Package Quantity (Metric)

500