

Specification Sheet

Part Number: 157-00331



1-Piece Cable Tie/Fir Tree Mount with Disc, 12.5mm Offset, 8.5"L, 6.1-7mm Hole, PA66HIRHS, Black, 2000/ctn

Article Number

157-00331

Type

T50ROSFT6SO12.5A

Color

Black (BK)

Features & Benefits

- Off-Set design allows bundles to sit off of mounting points to avoid friction against surrounding areas.
- Fir tree gives 3 to 1 extraction versus insertion force making them strong and easy to install.
- Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.

Quantity Per

bag

Product Description

HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Short Description

1-Piece Cable Tie/Fir Tree Mount with Disc, 12.5mm Offset, 8.5"L, 6.1-7mm Hole, PA66HIRHS, Black, 2000/ctn

Global Part Name

T50ROSFT6SO12.5A-PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

8.5

Length L (Metric)

215.5

Offset Length(Imperial)

0.49

Offset Length(Metric)

12.5

Identification Plate Position

none

Releasable Closure

No

Width W (Imperial)

0.19

Width W (Metric)

5.1

Bundle Diameter Min (Imperial)

0.08

Bundle Diameter Min (Metric)

1.6

Bundle Diameter Max (Imperial)

1.97

Bundle Diameter Max (Metric)

50.0

| | |
|------------------------------------------------|------------------------------------------------------------------|
| Thickness T (Metric) | 1.4 |
| Height H (Imperial) | 0.87 |
| Panel Thickness Min(Imperial) | 0.02 |
| Panel Thickness Max(Imperial) | 0.26 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 6.65 |
| Mounting Hole Diameter D (Imperial) | 0.24 - 0.28 ";0.24 - 0.26 |
| Mounting Hole Diameter D (Metric) | 6.5 mm 6.35 mm (hexagonal) |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Imperial) | 0.28 ";0.26 |
| Mounting Hole Diameter D Max (Metric) | 7.0 |
| Disc Diameter(Metric) | 15.0 |
| Disc Diameter (Imperial) | 0.59 |
| Material | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut | PA66HIRHS |
| ROHS Complaint | Yes |

Package Quantity (Metric)

500